

Appl. No. 10/551,444
Amendment dated: January 23, 2009
Reply to OA of: December 23, 2008

This listing of claims will replace all prior versions and listings of claims in the application.

Listing of Claims:

1(currently amended). An applying filler extruding container discharging an applying filler filled in a filling region within a container through a discharge port provided in a leading end of the container on the basis of forward movement of a movable body arranged within said container, comprising:

a leading tube formed in a tubular shape and having said discharge port at a leading end; and

a main body side assembly made by installing said movable body, an engagement portion of a male thread and a female thread for moving said movable body, and a rotation preventing portion of said movable body in a main body side tube portion formed in a tubular shape,

wherein an inner portion of said leading tube is formed as said filling region so as to be formed as a filling member in which said applying filler is filled, and the filling member in which the applying filler is filled is inserted to the leading end side of said main body side assembly so as to be attached to said main body side assembly,

wherein said rotation preventing portion in said main body side assembly is formed by engaging a main body tube having said female thread engaging with said male thread provided in an outer surface of said movable body, an operating tube coupled to a rear end side of said main body tube so as to be rotatable and immobile in an axial direction, a shaft body portion extended from a bottom portion of said operating tube and said movable body so as to be non-rotatable and movable in the axial direction, a locking portion provided in an outer surface in a rear half side of said filling member is coupled to a locking portion provided in an inner surface in a leading end side of said main body tube so as to be non-rotatable and immobile in the axial

Appl. No. 10/551,444
Amendment dated: January 23, 2009
Reply to OA of: December 23, 2008

direction, and said movable body is moved on the basis of a relative rotation of said operating tube and said main body tube or said filling member.

Claims 2-3(canceled).

4(currently amended). An applying filler extruding container as claimed in claim [[2]] 1, wherein said main body side assembly has a predetermined built-in engagement portion, and a built-in rotating amount regulating member having a concavo-convex portion arranged so as to face to the predetermined engagement portion in an axial direction and energized toward said predetermined engagement portion by an elastic portion, and said concavo-concave portion of said rotating amount regulating member and said predetermined engagement portion are engaged by click in accordance with a fixed amount relative rotation in forward and reverse directions between said filling member and the member coupling said filling member so as to be rotatable and immobile in the axial direction.

Claims 5-6(canceled).

7(currently amended). An applying filler extruding container as claimed in claim [[5]] 4, wherein said concavo-convex portion and said engagement portion constitute a ratchet mechanism allowing one-way rotation.

8(currently amended). An applying filler extruding container as claimed in claim [[2]] 1, wherein a plurality of concave portions depressed to the leading end side or a plurality of convex portions protruding to the rear side are provided in a rear end surface of said movable body along a peripheral direction, and a plurality of convex portions moving forward to said concave portions of said movable body at the maximum retreated time of said movable body so as to be engaged in the rotating direction, or a plurality of concave portions to which said convex portions of said movable body move

Appl. No. 10/551,444
Amendment dated: January 23, 2009
Reply to OA of: December 23, 2008

forward so as to be engaged in the rotating direction are provided in the bottom surface of the tube having said shaft body portion and a peripheral edge of said shaft body portion.

9(canceled).

10(currently amended). An applying filler extruding container as claimed in ~~any one of~~ claim 4, wherein a plurality of concave portions depressed to the leading end side or a plurality of convex portions protruding to the rear side are provided in a rear end surface of said movable body along a peripheral direction, and a plurality of convex portions moving forward to said concave portions of said movable body at the maximum retreated time of said movable body so as to be engaged in the rotating direction, or a plurality of concave portions to which said convex portions of said movable body move forward so as to be engaged in the rotating direction are provided in the bottom surface of the tube having said shaft body portion and a peripheral edge of said shaft body portion.

Claims 11-13(canceled).